

## CABLE BRACES

1/4" x 1" flat bar cable braces are used to support the cables between end or intermediate posts to keep the cable from flexing excessively when a load is applied. Cable braces are attached to the top rail and to the lower mounting surface, which can be a bottom rail or the deck. Available in mill finish carbon steel or #4 finish stainless steel.

Contact factory for **CABLE BRACE ORDER FORM**

## CABLE BRACE FLOOR PLATES

For mounting cable braces to top or bottom rail or deck.



Order Part No.	Material
FLP-CB	Mill Finish Carbon Steel
FLP-CBS	#4 Finish Stainless Steel

## STAINLESS STEEL SPACERS

Used between two structural steel posts or flat bars for a "double end post" type construction. .970" length.

Order Part No.	Outside Dia.	Wall Thickness	Use with Receivers & Welded Receivers:
SPC-R6	5/8"	.083"	1/8" and 3/16" diameter cable
SPC-R8	3/4"	.095"	1/4" diameter cable



## BEVELED WASHERS (for flat-sided frames only)

Made of stainless steel for use with Invisiware® Receivers and Radius Ferrules on stairways or slopes where you need to drill your end post holes at an angle. See our Ultra-tec® product catalog for how to avoid having to drill your holes at an angle using Invisiware® Receivers on stairways.

Order Part No.	Used with Cable Dia.	Stair/Slope Pitch
BW32-6	1/8" or 3/16"	30° - 33°
BW35-6	1/8" or 3/16"	34° - 36°
BW38-6	1/8" or 3/16"	37° - 39°
BW32-8	1/4"	30° - 33°
BW35-8	1/4"	34° - 36°
BW38-8	1/4"	37° - 39°

